

THIN CUTTING WHEELS METALYNX ULTAA ÜT

FEATURES:

- Lightning Fast Cuts 20% faster than the closest competitor
- Long Life maximize cuts per wheel, reducing change-overs and cost of use
- **Reduced Burrs** super smooth cuts create smaller, cleaner seams for easier welding
- Consistency A TRUE 1 mm thickness delivers consistency for precision cutting
- Greater Stability increased wheel density through SOLID CORE technology provides superior wheel stability and optimum safety

BEST ON: thin sheet metal, tubes, profiles, small cross-section rods



increases cutting speed and provides longer life, reduced friction, & superior stability

You can be thin and still be tough with Metalynx thin cutting wheels.



UltraCut thin cutting wheels deliver unmatched cutting performance and toughness with a TRUE 1 millimeter thickness. These ultra thin wheels deliver precise, clean cuts that are faster and smoother than conventional cutting wheels.

Proprietary SOLID CORE technology increases density of the wheels, resulting in longer life, reduced friction, and superior stability. From the first cut, operators will experience lightning fast, smooth cutting, and exceptional control for clean, precise cuts on thin sheet metal, profiles, and small diameter rods.



MAX INOX ULTRACUT

Contaminant-free* for stainless steel

				F41		F42	
Dimensions D x T x H mm	Grade	Speed m/s	Max. RPM min ⁻¹	Standard Pack pc/box	Item Number	Standard Pack pc/box	Item Number
115 x 0,75 x 22,23	UC20A60R-BF	80	13300	25	388474	25	412164
115 x 0,75 x 22,23				10/tin	388474T	_	_
115 x 1 x 22,23				25	388475	_	_
115 x 1 x 22,23				10/tin	388475T	_	_
125 x 0,75 x 22,23	UC20A60R-BF	80	12250	25	388478	_	_
125 x 0,75 x 22,23				10/tin	388478T	_	_
125 x 1 x 22,23				25	388479	_	_
125 x 1 x 22,23				10/tin	388479T	_	_
,							

^{*}Contaminant-free, less than 0.1% Fe, S, Cl



MAX INOX & METAL ULTRACUT

Fast cut and long life on metal.

				F41		F42	
Dimensions D x T x H mm	Grade	Speed m/s	Max. RPM min ⁻¹	Standard Pack pc/box	Item Number	Standard Pack pc/box	Item Number
115 x 0,75 x 22,23	UC20A60S-BF	80	13300	25	412168	_	
115 x 1 x 22,23				25	388455	_	_
115 x 1 x 22,23				10/tin	388455T	_	_
125 x 0,75 x 22,23	UC20A60S-BF	80	12250	25	412169	25	409223
125 x 1 x 22,23				25	388459	_	_
125 x 1 x 22,23				10/tin	388459T	_	_





