

POWER WIRE BRUSHES



Knot wire wheels are used on angle grinders for tough cleaning jobs. Featuring Weiler's individual knot hole construction, these radial brushes are available in heat-treated steel and type 302 stainless steel.

APPLICATIONS:

- Weld preparation and cleaning
- Cleaning scale and heavy corrosion
- Removing heavy burrs from large pieces after cutting

KNOT WHEEL BRUSHES

Steel and stainless wire

| Diameter mm | Wire Size mm | Arbor | Thickness mm | Max. RPM min ⁻¹ | Standard Pack pc/box | Item Number | |
|----------------|-----------------|--------|-----------------|-------------------------------|-------------------------|-------------|-----------|
| | | | | | | Steel | Stainless |
| 115 | 0.5 | X-LOCK | 12 | 12500 | 10 | 388067 | — |



388067

Cup brushes are used on portable tools for cleaning large surfaces faster than a wheel brush.

APPLICATIONS:

- Removing paint and coatings
- Cleaning rust, scale, and corrosion
- Deburring
- Weld prep and cleaning

KNOT CUP BRUSHES

Steel and stainless wire / Hurricane twist

| Diameter mm | Wire Size mm | Arbor | Max. RPM min ⁻¹ | Standard Pack pc/box | Item Number | |
|----------------|-----------------|--------|-------------------------------|-------------------------|-------------|-----------|
| | | | | | Steel | Stainless |
| 75 | 0.5 | X-LOCK | 11000 | 1 | 388068 | — |



388068

CRIMPED CUP BRUSHES

Steel and stainless wire

| Diameter mm | Wire Size mm | Arbor | Max. RPM min ⁻¹ | Standard Pack pc/box | Item Number | |
|----------------|-----------------|--------|-------------------------------|-------------------------|-------------|-----------|
| | | | | | Steel | Stainless |
| 75 | 0.3 | X-LOCK | 12500 | 1 | 388069 | — |



388069

THE WEILER PROMISE

At Weiler, we passionately embrace change to improve our products and our processes to move the company and our customers forward. By bringing new ideas and creative problem solving together in an open, collaborative environment, we will improve our customers' productivity and create profitable growth.



WEILER ABRASIVES GROUP

Weiler Abrasives
One Weiler Drive
Cresco, PA 18326 USA

Weiler de México
Querétaro, México

Weiler do Brasil
Vinhedo, Brasil

Weiler Abrasives
Bindlach, Germany

Weiler Abrasives
Slovenia
• Maribor
• Zreče
• Loče

ID # 405750

WEILER ABRASIVES, d.o.o. | Titova cesta 60, SI- 2000 Maribor | info.slovenia@weilerabrasives.com



www.weilerabrasives.com/emea/



X-LOCK

THE ULTIMATE CHANGING SYSTEM EASIER THAN EVER / ONE SIMPLE CLICK

Lightning Fast Changeovers:

With a 5 times faster changeover time, X-LOCK accessories spend more time on the job and less time on the bench.

No Complexity:

X-LOCK tools require no tools or adapters to mount. There is nothing to lose or misplace.

User Protection:

An audible "CLICK" tells the user that the disc is properly fastened.

Universal Attachment:

X-LOCK accessories can be mounted on X-LOCK tools as well as standard angle grinders.



CUTTING FOR X-LOCK ANGLE GRINDERS



Our diverse line of cutting wheels provides consistent, well-balanced, high-performance solutions for the professional who wants to get the most demanding jobs done right and fast.



MAX INOX & METAL Cutting Wheels

Contaminant-free* for stainless steel



404198

| Dimensions D x T x H mm | Grade | Speed m/s | Max. RPM min ⁻¹ | F41 | | F42 | |
|-------------------------------|------------|--------------|-------------------------------|-------------------------|----------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number | Standard Pack pc/box | Item Number |
| 115 x 1,0-X-LOCK | E20A60S-BF | 80 | 13300 | 25 | 404196 | — | — |
| 115 x 1,6-X-LOCK | E20A46S-BF | | | | 404206 | — | — |
| 115 x 2,5-X-LOCK | E20A30R-BF | | | | 404207 | 25 | 404210 |
| 125 x 1,0-X-LOCK | E20A60S-BF | 80 | 12250 | 25 | 404198 | — | — |
| 125 x 1,6-X-LOCK | E20A46S-BF | | | | 404208 | — | — |
| 125 x 2,5-X-LOCK | E20A30R-BF | | | | 404209 | 25 | 404211 |

*Contaminant-free, less than 0.1% Fe, S, Cl



MAX METAL Cutting Wheels

Fast cut and long life on metal.



404197

| Dimensions D x T x H mm | Grade | Speed m/s | Max. RPM min ⁻¹ | F41 | | F42 | |
|-------------------------------|----------|--------------|-------------------------------|-------------------------|----------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number | Standard Pack pc/box | Item Number |
| 115 x 1,0-X-LOCK | EA60T-BF | 80 | 13300 | 25 | 404195 | — | — |
| 115 x 1,6-X-LOCK | EA46T-BF | | | | 404199 | — | — |
| 115 x 2,5-X-LOCK | EA30T-BF | | | | 404200 | 25 | 404203 |
| 125 x 1,0-X-LOCK | EA60T-BF | 80 | 12250 | 25 | 404197 | — | — |
| 125 x 1,6-X-LOCK | EA46T-BF | | | | 404201 | — | — |
| 125 x 2,5-X-LOCK | EA30T-BF | | | | 404202 | 25 | 404204 |



Metalynx Pro cutting wheels deliver a fast cut rate and consistent performance at great value. An aggressive, hard-working product line for everyday general purpose use.



PRO INOX & METAL Cutting Wheels

Contaminant-free* for stainless steel



400776

| Dimensions D x T x H mm | Grade | Speed m/s | Max. RPM min ⁻¹ | F41 | | F42 | |
|-------------------------------|-----------|--------------|-------------------------------|-------------------------|----------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number | Standard Pack pc/box | Item Number |
| 115 x 1,0-X-LOCK | 20A60R-BF | 80 | 13300 | 25 | 404193 | — | — |
| 115 x 1,6-X-LOCK | 20A46R-BF | | | | 407634 | — | — |
| 115 x 2,5-X-LOCK | 20A30R-BF | | | | 407636 | 25 | 407635 |
| 125 x 1,0-X-LOCK | 20A60R-BF | 80 | 12250 | 25 | 400776 | — | — |
| 125 x 1,6-X-LOCK | 20A46R-BF | | | | 400777 | — | — |
| 125 x 2,5-X-LOCK | 20A30P-BF | | | | 403725 | 25 | 407637 |

*Contaminant-free, less than 0.1% Fe, S, Cl



PRO METAL Cutting Wheels

Fast cutting on metal.



400778

| Dimensions D x T x H mm | Grade | Speed m/s | Max. RPM min ⁻¹ | F41 | | F42 | |
|-------------------------------|---------|--------------|-------------------------------|-------------------------|----------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number | Standard Pack pc/box | Item Number |
| 115 x 1,0-X-LOCK | A60S-BF | 80 | 13300 | 25 | 407638 | — | — |
| 115 x 1,6-X-LOCK | A46S-BF | | | | 407639 | — | — |
| 115 x 2,5-X-LOCK | A30S-BF | | | | 407641 | 25 | 407640 |
| 125 x 1,0-X-LOCK | A60S-BF | 80 | 12250 | 25 | 407642 | — | — |
| 125 x 1,6-X-LOCK | A46S-BF | | | | 407643 | — | — |
| 125 x 2,5-X-LOCK | A30S-BF | | | | 400778 | 25 | 407644 |



Metalynx grinding wheels help Metal Fabrication professionals get the most demanding jobs done right and done fast.

FEATURES:

- Ceramic grinding wheels deliver the **fastest grinding with the least effort**
- Triple fiberglass reinforcement** provides added strength for aggressive stock removal
- INOX is ideal for **stainless steel** and other hard-to-grind metals



MAX INOX & METAL Grinding Wheels

Contaminant-free* for stainless steel



404212

| Dimensions D x T x H mm | Grade | Speed m/s | Max. RPM min ⁻¹ | F27 | |
|-------------------------------|------------|--------------|-------------------------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number |
| 115 x 6,5-X-LOCK | E20A24R-BF | 80 | 13300 | 10 | 407645 |
| 125 x 6,5-X-LOCK | E20A24R-BF | | | 10 | 404212 |

*Contaminant-free, less than 0.1% Fe, S, Cl



MAX METAL Grinding Wheels

Fast grinding and long life on metal.



404205

| Dimensions D x T x H mm | Grade | Speed m/s | Max. RPM min ⁻¹ | F27 | |
|-------------------------------|----------|--------------|-------------------------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number |
| 115 x 6,5-X-LOCK | EA24S-BF | 80 | 13300 | 10 | 407646 |
| 125 x 6,5-X-LOCK | EA24S-BF | | | 10 | 404205 |



Metalynx Pro grinding wheels deliver consistent performance and fast grinding at a great value. An aggressive, hard working product line for every day general purpose use.



PRO INOX & METAL Grinding Wheels

Contaminant-free* for stainless steel



403726

| Dimensions D x T x H mm | Grade | Speed m/s | Max. RPM min ⁻¹ | F27 | |
|-------------------------------|-----------|--------------|-------------------------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number |
| 115 x 6,5-X-LOCK | 20A24P-BF | 80 | 13300 | 10 | 407647 |
| 125 x 6,5-X-LOCK | 20A24P-BF | | | 10 | 403726 |

*Contaminant-free, less than 0.1% Fe, S, Cl



PRO METAL Grinding Wheels

Fast grinding on metal.



400779

| Dimensions D x T x H mm | Grade | Speed m/s | Max. RPM min ⁻¹ | F27 | |
|-------------------------------|---------|--------------|-------------------------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number |
| 115 x 6,5-X-LOCK | A24S-BF | 80 | 13300 | 10 | 407648 |
| 125 x 6,5-X-LOCK | A24S-BF | | | 10 | 400779 |

FLAP DISCS FOR X-LOCK GRINDERS



Maximize productivity with a superior combination of life and grinding speed. Ceramic and zirconia alumina grain options provide cool, fast-grinding action, allowing you to do more work more quickly. The Discs are contaminant-free and contain less than 0.1% Iron, Sulfur, and Chlorine.



MAX CERAMIC Flap Discs

Ceramic Alumina / Phenolic Backing / Contaminant-free* for stainless steel



401201

| Dimensions D x H mm | Grit | Speed m/s | Max. RPM min ⁻¹ | F29 | |
|---------------------------|------|--------------|-------------------------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number |
| 115-X-LOCK | 40 | 80 | 13300 | 10 | 401199 |
| 115-X-LOCK | 60 | | | 10 | 401200 |
| 125-X-LOCK | 40 | 80 | 12250 | 10 | 401201 |
| 125-X-LOCK | 60 | | | 10 | 401202 |

*Contaminant-free, less than 0.1% Fe, S, Cl



MAX ZIRC Flap Discs

Zirconia Alumina / Phenolic Backing / Contaminant-free* for stainless steel



401196

| Dimensions D x H mm | Grit | Speed m/s | Max. RPM min ⁻¹ | F29 | |
|---------------------------|------|--------------|-------------------------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number |
| 115-X-LOCK | 40 | 80 | 13300 | 10 | 401191 |
| 115-X-LOCK | 60 | | | 10 | 401192 |
| 115-X-LOCK | 80 | | | 10 | 401193 |
| 115-X-LOCK | 120 | | | 10 | 401194 |
| 125-X-LOCK | 40 | 80 | 12250 | 10 | 401195 |
| 125-X-LOCK | 60 | | | 10 | 401196 |
| 125-X-LOCK | 80 | | | 10 | 401197 |
| 125-X-LOCK | 120 | | | 10 | 401198 |

*Contaminant-free, less than 0.1% Fe, S, Cl



Metalynx Pro flap discs are designed to deliver performance, consistency and reliability when grinding and finishing metal. The Discs are contaminant-free and contain less than 0.1% Iron, Sulfur, and Chlorine.



PRO ZIRC Flap Discs

Zirconia Alumina / Phenolic Backing / Contaminant-free* for stainless steel



401183

| Dimensions D x H mm | Grit | Speed m/s | Max. RPM min ⁻¹ | F29 | |
|---------------------------|------|--------------|-------------------------------|-------------------------|----------------|
| | | | | Standard Pack pc/box | Item Number |
| 115-X-LOCK | 40 | 80 | 13300 | 10 | 401183 |
| 115-X-LOCK | 60 | | | 10 | 401184 |
| 115-X-LOCK | 80 | | | 10 | 401185 |
| 115-X-LOCK | 120 | | | 10 | 401186 |
| 125-X-LOCK | 40 | 80 | 12250 | 10 | 401187 |
| 125-X-LOCK | 60 | | | 10 | 401188 |
| 125-X-LOCK | 80 | | | 10 | 401189 |
| 125-X-LOCK | 120 | | | 10 | 401190 |

*Contaminant-free, less than 0.1% Fe, S, Cl